



SEMI AUTOMATIC RANDOM BOTTOM SEALER RS20 COMPARISON CHART



**WANT TO KNOW MORE
ABOUT THIS MACHINE?**

SCAN HERE TO LEARN MORE ABOUT THIS MACHINE

STANDARD MODEL INFORMATION:

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)	POWER REQUIREMENTS	AIR REQUIREMENTS
RS20-2 2" Tape Head	(42.9") x (30.0") x (28.8")	(6.0" - U) x (4.25" - 20.0") x (4.0+")	(20.5" - 30.0")	Up to 15	318	110 Volts 60 Hz	80 PSI, 5SCFM

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)	POWER REQUIREMENTS	AIR REQUIREMENTS
RS20-2 2" Tape Head	(42.9") x (30.0") x (28.8")	(6.0" - U) x (4.25" - 20.0") x (4.0+")	(20.5" - 30.0")	Up to 15	318	110 Volts 60 Hz	80 PSI, 5SCFM
RS20-3 3" Tape Head	(42.9") x (30.0") x (28.8")	(6.0" - U) x (5.25" - 21.0") x (4.0+")	(20.5" - 30.0")	Up to 15	318	110 Volts 60 Hz	80 PSI, 5SCFM
RS30-2 2" Tape Head	(42.9") x (39.4") x (28.8")	(6.0" - U) x (4.25" - 30.0") x (4.0+")	(20.5" - 30.0")	Up to 15	380	110 Volts 60 Hz	80 PSI, 5SCFM
RS30-3 3" Tape Head	(42.9") x (39.4") x (28.8")	(6.0" - U) x (5.25" - 31.0") x (4.0+")	(20.5" - 30.0")	Up to 15	380	110 Volts 60 Hz	80 PSI, 5SCFM

INFORMATION SUBJECT TO CHANGE WITHOUT NOTICE.

***OUTSIDE DIMENSIONS ONLY
U - UNLIMITED**