



AUTOMATIC TOP & BOTTOM 4-EDGE SEALER AT4E COMPARISON CHART



**WANT TO KNOW MORE
ABOUT THIS MACHINE?**

SCAN HERE TO LEARN MORE ABOUT THIS MACHINE

STANDARD MODEL INFORMATION:

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)	POWER REQUIREMENTS	AIR REQUIREMENTS
AT4E 22-2 2" Tape Head	(78.9") x (48.5") x (63.0")	(10.3" - 20.0") x (9.8" - 20.0") x (9.8" - 20.0")	Determined at the time of order	Up to 8	1,470	110 Volts 60 Hz	80 PSI, 10 SCFM

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)	POWER REQUIREMENTS	AIR REQUIREMENTS
AT4E 22-3 3" Tape Head	(78.9") x (48.5") x (63.0")	(10.3" - 20.0") x (9.8" - 20.0") x (9.8" - 20.0")	Determined at the time of order	Up to 8	1,470	110 Volts 60 Hz	80 PSI, 10 SCFM
AT4E 22-2 2" Tape Head	(78.9") x (48.5") x (63.0")	(10.3" - 20.0") x (9.8" - 20.0") x (9.8" - 20.0")	Determined at the time of order	Up to 8	1,470	110 Volts 60 Hz	80 PSI, 10 SCFM