



MBD STAINLESS


MANUAL BOTTOM DRIVE (STAINLESS STEEL)

The BestPack™ MBD 304 Stainless Steel Series are operator-fed, adjustable, carton-sealing machines designed to cater to the needs of light to heavy duty, uniform carton closure applications where there are wet environments. Units are available for either splash resistant or wash-down applications. The two bottom belts are driven by one bottom drive electric 110V UL approved motor.

The food grade 304 stainless steel allows for approved food grade applications. The tape head also comes standard in food grade 304 stainless steel for 21 CFR 110 compliance.



OPERATOR REQUIRED



UNIFORM CARTONS



TOP & BOTTOM SEAL

110 VOLTS 60 HZ

Power Requirements

UP TO 20 CPM

Speed


N/A

Air Requirements

320 LBS

Shipping Weight

CARTON RANGE



Length (min. - max.)
(6.0" - U)

Width (min. - max.)
(6.5" - 20.0")

Height (min. - max.)
(3.0" - 20.25")

Specifications based on MBD22-2S

STANDARD FEATURES

- Heavy Duty 2mm Food Grade 304 Stainless Steel Welded Frame Including Upper Welded Legs
- Offset Top Tape Heads for Top and Bottom Sealing Cartons Down to 3.0" Tall
- Bottom Belt Drive System with 1-piece Die Molded Belts and V-belt Guide
- Bottom Belt Drive System also Includes Idler Rollers Behind the Belts
- 3" Tape Head Unit Accepts Either 2" and 3" Pop-out BestPack High Speed Tape Heads
- Top Mast Design with Screw Drive Shafts and an Upper Side Compression Unit
- Adjustable Bed Height from 23.5" to 30.0"
- Width Adjustment Uses Self-centering Side Guide Rails
- Height Adjustment Handle can be Mounted on Either Side of the Carton Sealer
- Electrical Box is Mounted on the Left Side of the Sealer
- Tape Roll Lengths: 1,000 yd., 1,500 yd., 2,000 yd.
- Extra 4" Carton Height Adjustment Available on Upper Assembly
- Quality UL Approved Electrical Parts

OPTIONS

- Food Grade 304 Stainless Steel Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Food Grade 304 Stainless Steel Heavy Duty Dual Locking Casters
- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Aluminum Frame Interlock Safety Gates
- Motorized Height Adjustment

EXTRA ACCESSORIES TO IMPROVE EFFICIENCY



FOOD GRADE 304 STAINLESS STEEL LOCKING CASTERS

The heavy duty locking casters allow the carton sealer quick and easy mobility to other locations.



304 STAINLESS STEEL SPARE TAPE HEAD

Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



FOOD GRADE 304 STAINLESS STEEL LONG INFEEED/EXIT CONVEYOR W/ UNIQUE L-BRACKET

This 39.5" long or 19.75" short conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



SAFETY GATES

Aluminum frame interlock safety gates can be added to the carton sealer for an extra layer of protection. These interlock safety gates protect the operator from all of the moving parts of the carton sealer.



SPARE PARTS KIT

Spare Parts Kits may vary based on machine

Minimize downtime with BestPack's Spare Parts Kit.



HIGH SPEED MOTOR

High Speed Motor Upgrade (up to 125 ft.)



CARTON SEALING TAPE

Put high quality tape on your BestPack Carton Sealer. Make sure to order machine length rolls for your new carton sealer.

POPULAR MBD-S MODELS

Please refer to comparison chart for complete list of models.

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.**	SHIPPING WEIGHT (LBS)
MBD22-2S 2" Tape Head	(42.0") x (28.8") x (70.3")	(6.0" - U) x (6.5" - 20.0") x (3.0" - 20.25")	(23.5" - 30")	Up to 20	320
MBD22-3S 3" Tape Head	(42.0") x (28.8") x (70.3")	(6.0" - U) x (7.5" - 20.0") x (3.0" - 20.25")	(23.5" - 30")	Up to 20	320

Information subject to change without notice.

U - Unlimited
* Outside Dimensions Only
** Based on Customer Application



For more information please go to:
WWW.BESTPACK.COM or call us at **1.888.588.2378**