



BESTPACK



MANUAL TOP DRIVE LOW PROFILE MTLW COMPARISON CHART



WANT TO KNOW MORE
ABOUT THIS MACHINE?

SCAN HERE TO LEARN MORE ABOUT THIS MACHINE

STANDARD MODEL INFORMATION:

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)	POWER REQUIREMENTS	AIR REQUIREMENTS
MTLW22-2 2" Tape Head	(46.1") x (33.5") x (59.1")	(6.0" - U) x (8.2*** - 19.7") x (0.5" - 20.3")	(20.5" - 30.0")	Up to 40	388	110 Volts 60 Hz	60-75 PSI, 2-3 SCFM

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)	POWER REQUIREMENTS	AIR REQUIREMENTS
MTLW22-2 2" Tape Head	(46.1") x (33.5") x (59.1")	(6.0" - U) x (8.2*** - 19.7") x (0.5" - 20.3")	(20.5" - 30.0")	Up to 40	388	110 Volts 60 Hz	60-75 PSI, 2-3 SCFM
MTLW22-3 3" Tape Head	(46.1") x (33.5") x (59.1")	(6.0" - U) x (8.2*** - 19.7") x (0.5" - 20.3")	(20.5" - 30.0")	Up to 40	388	110 Volts 60 Hz	60-75 PSI, 2-3 SCFM
MTLW32-2 2" Tape Head	(46.1") x (43.0") x (59.1")	(6.0" - U) x (8.2*** - 30.0") x (0.5" - 20.3")	(20.5" - 30.0")	Up to 40	416	110 Volts 60 Hz	60-75 PSI, 2-3 SCFM
MTLW32-3 3" Tape Head	(46.1") x (43.0") x (59.1")	(6.0" - U) x (8.2*** - 30.0") x (0.5" - 20.3")	(20.5" - 30.0")	Up to 40	416	110 Volts 60 Hz	60-75 PSI, 2-3 SCFM

INFORMATION SUBJECT TO CHANGE WITHOUT NOTICE.

*OUTSIDE DIMENSIONS ONLY

U - UNLIMITED

** BASED ON CUSTOMER APPLICATION