



*Model Shown: C-Series C-250H

C-SERIES

HORIZONTAL FLOW WRAPPERS


Great for Wrapping Cookies, Muffins, Candy Bars, Biscuits, Brownies, etc.

PRODUCTION
RATE:
up to 40-100 ppm

MAX FILM
WIDTH:
(9.8")

MACHINE DIMENSIONS:
(L x W x H)
(148.0" x 26.0" x 56.0")

SEAL DIMENSIONS:
(L x W x H)
(13.0" x 4.2" x 2.0")



Specifications based on C-250H

The C-Series flow wrappers are used by many bakery, confectionary and cannabis manufacturers. Designed with a twin-motor drive, it is considered one of the most economical and easy to use flow wrappers of its generation. Standard features include photo eye for print registered film. Available options include nitrogen gas flush, embedded labelers, date coding, adjustable forming plows and more.

HORIZONTAL FLOW WRAPPERS

STANDARD FEATURES INCLUDE

- Mechanical Drive
- Touch Screen Menu with Auto Diagnostics & Error Display
- Product Counter
- 6.5 ft Flighted Infeed Conveyor
- One Step Adjustment of Bag Length
- Print Registration

OPTIONS:

- Teflon Coated Seal Jaws
- Right To Left Product Flow
- Stainless Steel Frame Construction
- Photo Electric Eye (for printed film included)
- All Color Photo Sensor
- Adjustable Film Forming Device
- Additional Fixed Forming Device
- Dual Seal Jaw (standard on C-250H)
- Triple Seal Jaw
- Powered Discharge Wheel on Exit Conveyor
- Gas Flush-Control Valves and Pipes
- Gusseted Bag Device
- Plastic Product Carriers
- Single Head Label Applicator LBL-110 (Label Applicator apply label up to 4.3" x 4.3")
- Dual Head Label Applicator
- Hot Ink Roller Coder
- Hot Ink Ribbon Coder-THR40A
- Elfin 1S Ink Jet Printer (Includes Mounting Hardware)
- Thermal Transfer Ribbon (33mm x 500m or 55mm x 900m)
- Videojet 6330 Thermal Transfer Printer
- Extended Infeed Conveyor-Std Length
- Paper Side Guides on Infeed Decking
- Stainless Steel Infeed Chain
- Hole Punch - Round
- Hole Punch - Euro Slot/Butterfly
- Hole Punch - Tear Notch "V"
- Pin Wheel Hole Punch (one row of pins)
- Stainless Steel Discharge Chute
- End Seal Chain Conveyor
- Manufactured to Meet UL Requirements
- CE Certification
- External Start/Stop Switch (mounted to infeed conveyor)
- No Product-No Cycle function
- Drop Chute
- Right Angle Horizontal Belted Infeed
- Increase Seal Jaw Height of C-350H to 3.1" (80mm)

POPULAR HORIZONTAL FLOW WRAPPERS MODELS

MODEL	SPEED	SEAL JAW WIDTH	BAG LENGTH	BAG WIDTH	FILM WIDTH	MAX PRODUCT HEIGHT
C250H Single Jaw	(40 to 100ppm)	(4.3")	(3.5"-13.0")	(1.25"-4.2")	(3.5"-9.8")	(2.0")
C250H Dual Jaw	(40 to 125ppm)	(4.3")	(2.9"-8.6")	(1.25"-4.2")	(3.5"-9.8")	(2.0")
C250H Triple Jaw	(40 to 150ppm)	(4.3")	(2.5"-4.5")	(1.25"-4.2")	(3.5"-9.8")	(1.5")
C350H Single Jaw	(40 to 100ppm)	(7")	(3.5"-13.0")	(2"-6.25")	(5"-13.75")	(2.5")
C350H Dual Jaw	(40 to 125ppm)	(7")	(2.9"-8.6")	(2"-6.25")	(5"-13.75")	(2.5")
C450H Single Jaw	(40 to 100ppm)	(9")	(6.3"-18.9")	(2.2"-7.8")	(6"-17.5")	(4")
C450P**	(40 to 115ppm)	(9")	(5"-17.5")	(2.2"-7.8")	(6"-17.5")	(4")
C600H	(30 to 75ppm)	(11")	(6.3"-18.9")	(2.5"-10.5")	(6"-23.5")	(4")
C680	(30 to 100ppm)	(13.4")	(7.8"-23.6")	(4.5"-13")	(26.7" max)	(4")

Information subject to change without notice.

**Model C450P - is capable of running Polyolefin Shrink Film