



Model Shown: PP-48ST

ST SERIES

ALL-IN-ONE COMBO L-BAR SEALER


Semi-Automatic L-Sealer and Hooded Shrink Chamber in one complete unit.

PRODUCTION RATE:
up to 5 ppm

MAX FILM WIDTH:
(20.0")

MACHINE DIMENSIONS:
(L X W)
(50.0" x 26.0")

SEAL DIMENSIONS:
(L X W)
(12.0" x 18.5")



Specifications based on PP-48ST

With the Dual Magnetic Hold Down, the operator simply lowers the hooded chamber and the magnets apply the seal pressure to produce great seals and eliminate operator fatigue. The magnets hold the chamber closed during the shrink cycle and release when the shrink cycle is complete. Adjustable grate lowers 3.5" to accept taller products.

AVAILABLE MODELS:

- PP-48ST-110V
- PP-48AT-220V
- PP-76ST
- PP-76STC
- PP-76ST-SS
- PP-77ST

SEMI-AUTOMATIC SEALERS

STANDARD FEATURES INCLUDE:

- Band seal technology
- Dual magnetic hold down for seal and shrink cycle
- Pinwheel hole punch
- Locking casters

POPULAR SEMI-AUTOMATIC SEALER MODELS

MODELS	SEALING DIMENSIONS (LENGTH x WIDTH x HEIGHT)	MAX PACKAGING HEIGHT	POWER REQUIREMENTS	MAX FILM WIDTH
PP-48ST-110V	(12.0" x 18.5")	(6.0")	110 Volts 20 AMPS 1 Phase	(20.0")
PP-76ST-220V	(16.0" x 22.0")	(8.0")	220 Volts 25 AMPS 1 Phase	(24.0")

Information subject to change without notice.